

## Upper section, Linearis Compact L: 550 mm, Sys 100, 304 SST cover, K 3

### Article information

Item no.: 47806S  
GTIN: 4026092079928  
Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

### Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

#### Variant

|  |   |
|--|---|
| System:  | 100   |
| Seepage opening:   | yes   |
| Waterproofing layer on the upper section:                                | Enclosed sealing collar to be glued (bd) according to DIN 18534 |
| Water exposure class in accordance to DIN 18534-1 (up to and including): | W3-I  |
| Sealing water height:  | 50 mm   |
| Discharge rate (l/s) with 10 mm threshold:                               | 0,6   |
| Discharge rate (l/s) without threshold:                                  | 0,5 mm  |

#### General characteristics

|                      |          |
|----------------------|----------|
| Nominal size (DN):   | 100      |
| Outer diameter (OD): | 100 mm   |
| ATEX:                | no       |
| Odour trap:          | included |

#### Dimensions

|                          |             |
|--------------------------|-------------|
| Net weight:              | 1,56 kg     |
| Gross weight:            | 1,97 kg     |
| Outer dimension, length: | 615 mm      |
| Installation depth:      | 80 - 140 mm |
| Width:                   | 136 mm      |
| Height:                  | 77 mm       |
| Packaging dimension:     | length      |
| Packaging dimension:     | width       |

|                         |                       |
|-------------------------|-----------------------|
| Packaging dimension:    | height                |
| Coverage features       |                       |
| Type of cover:          | Stainless steel cover |
| Cover material:         | Stainless steel 14301 |
| Colour of cover:        | silver                |
| Frame material:         | Stainless steel 14301 |
| Load class:             | K 3 (EN 1253-1)       |
| Grating design:         | optionally tileable   |
| Rim width:              | 66 mm                 |
| Rim length:             | 550 mm                |
| Upper section material: | ABS                   |