

Scada wall drain w/cov, Wave, 304 SST, fixed w/prf membrn

Article information

Item no.: 48000.03M
GTIN: 4026092079133
Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory
- Alternative odour trap Multistop

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant

Lighting:

Waterproofing layer on the drain body:

Water exposure class in accordance to DIN 18534-1 (up to and including):

Sealing water height:

Discharge rate (l/s) with 20 mm threshold:

without

Factory-fitted sealing collar (WaD) according to DIN 18534

W3-I

22 mm

0,5

General characteristics

Nominal size (DN):

Outer diameter (OD):

Odour trap:

50

58 mm

included

Dimensions

Net weight:

Gross weight:

Length:

Width:

Height:

Packaging dimension:

Packaging dimension:

Packaging dimension:

1,86 kg

2,35 kg

362 mm

195 mm

353 mm

length

width

height

Tank/drain body

Number of outlets:

Material of drain body:

1

ABS

Coverage features

Type of cover:	Scada drain cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Height of cover:	74 mm
Length of cover:	312 mm
Min. flooring height:	15 mm
Surface:	Brushed SST
Frame material:	ABS
Locking:	inserted
Grating design:	Wave
Max. flooring height:	19 mm
Shape of upper section:	square
Upper section material:	ABS