

Roof drain Ecoguss Press fl., waterpr conc, DN70, w/o heat

Article information

Item no.: 48370.01
GTIN: 4026092039335
Price group: 40

Advantages

- Made of recyclable composite
- Permanently corrosion-free surface

Description

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Variant

System:	200
Heating:	without
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)

General characteristics

Standard:	EN 1253
Nominal size (DN):	70
Outer diameter (OD):	78 mm

Dimensions

Vertical adjustment:	40 - 140 mm
Net weight:	4,8 kg
Gross weight:	5,58 kg

Diameter:	365 mm
Cutout dimension, width:	227 mm
Cutout dimension, length:	227 mm
Type of height adjustability:	vertically adjustable upper section
Length:	365 mm
Width:	365 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Material of drain body:	Ecoguss
Coverage features	
Type of cover:	Gravel trap
Cover material:	Polymer
Colour of cover:	black
Upper section material:	Ecoguss