

Replacement pump Aquadive GTF1200 without float switch, 10 m

Article information

Item no.: 680595
GTIN: 4026092078815
Price group: 90

Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 11,19 kg

Gross weight: 11,19 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

Pumping device

Pump: GTF 1200

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V

Mains frequency: 50 Hz

Rated current: 6,2 A

Protection class: I

Insulation class: F

Cos phi - power factor: 0,98

Protection class (pump): IP 68

Temperature monitoring: integrated

Max. temperature (permanent) of conveyed material: 35 °C

Max. pumping height: 9 m

Speed: 2650 U/min

Power P1: 1,4 kW

Power P2: 0,84 kW

Operating mode: S1

Type of fuse required (electrical protection): Fuse protection through control unit 230 V

Type of pump connection cable: H07RN-F 3G 1.5 mm²

Length of mains cable for pump: 5 m

Control

Connection type:

Schuko (earthed contact) 2-pin

Type of fuse required (electrical protection):

Fuse protection through control unit 230 V