

Backwater valve Staufix Basic DN 200, Type 1, with emergency closure

Article information

Item no.: 72200
GTIN: 4026092002384
Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

Variant

| | |
|---|-----|
| Stainless steel flap as rat protection: | no |
| Emergency closure: | yes |
| Mechanical backwater flaps: | 1 |

General characteristics

| | |
|-------------------------|-----------------------|
| Colour: | black |
| Standard: | EN 13564 |
| Nominal size (DN): | 200 |
| Outer diameter (OD): | 200 mm |
| Type of wastewater: | without sewage |
| Installation situation: | exposed drainage pipe |
| Delivery state: | installation-ready |
| Backwater protection: | Type 1 |

Dimensions

| | |
|---|--------|
| Net weight: | 2,6 kg |
| Gross weight: | 2,6 kg |
| Vertical drop between inlet and outlet: | 9 mm |
| Length: | 530 mm |
| Width: | 248 mm |
| Height: | 328 mm |
| Packaging dimension: | length |

Packaging dimension:

width

Packaging dimension:

height

Coverage features

Cover locking:

screwed