

Yard drain System 400, DN 100, B, 380 - 510 mm

Article information

Item no.: 851100B
GTIN: 4026092004265
Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

Variant

System: 400
Heating: without
Contents of sludge trap: yes
Discharge rate (l/s) with 20 mm threshold: 4,5

General characteristics

Colour: black
Standard: EN 752
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: no

Dimensions

Net weight: 12,5 kg
Gross weight: 12,5 kg
Groundwater resistant from lower edge of base section: 500 mm
Cutout dimension, width: 535 mm
Cutout dimension, length: 585 mm
Min. insertion depth: 55 mm
Installation depth: 380 - 510 mm
Type of height adjustability: vertically adjustable upper section
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body
Number of outlets: 1
Material of drain body: Polymer
Socket version: lateral

Coverage features

Type of cover: Round slotted cover
Cover material: Grey iron
Colour of cover: black
Width of cover: 400 mm
Length of cover: 400 mm
Surface: EDM
Load class: B 125 (EN 124)
Rim width: 400 mm
Rim length: 400 mm
Shape of upper section: square
Contents of sludge trap: yes