

Chamber module LW 1000 floor slab Access LW 600, 2880-3129 mm, Class D

Article information

Item no.: 8740061
GTIN: 4026092065761
Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

Variant

Note on installation depth: A load distribution slab must be installed on site for load class D

General characteristics

Colour: black
Material: PE-HD
Standard: EN 13598-2
Installation situation: underground installation
Delivery state: Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval: Z-42.1-527
ATEX: no

Dimensions

Net weight: 214 kg
Gross weight: 247 kg
Groundwater resistant from lower edge of base section: 3000 mm
Installation depth: 2880 - 3129 mm
Type of height adjustability: vertically adjustable upper section

Length: 1200 mm
Width: 1200 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body
Inlet max. scoring (DN): 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 600 mm

Coverage features

Type of cover: Round cover plate
Cover material: Grey iron
Colour of cover: black
Width of cover: 659 mm
Height of cover: 122 mm
Length of cover: 659 mm
Surface: Grey iron
Locking: locked
Load class: D 400 (EN 124)
Tightness: surface water resistant