

Sampling chamber LW 400, DN 100/150, class B

Article information

Item no.: 915880B
GTIN: 4026092025055
Price group: 60

Description

Sampling chamber LW 400 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length.

| | |
|--|---|
| Flow direction: | straight |
| General characteristics | |
| Colour: | black |
| Material: | PE |
| Dimensions | |
| Net weight: | 25 kg |
| Gross weight: | 30 kg |
| Vertical drop between inlet and outlet: | 120 mm |
| Installation depth: | 400 - 1300 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Distance pipe bottom inlet to tank bottom: | 120 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 mm |
| Inlet nominal size (OD): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Clear width of tank (LW): | 400 mm |
| Coverage features | |
| Type of cover: | Cover plate |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Load class: | B 125 (EN 124) |
| Tightness: | odour-tight and surface water resistant |