

Grease separat. EasyClean Modular free, NS 1, Standard, 3-part, TS

Article information

Item no.: 93001-R2-TS
GTIN: 4026092103982
Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Chamber system: | three-piece chamber |
| Disposal variant: | Standard |
| Shredder-Mix-System: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 1 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Standard: | EN 1825 |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|--|--------|
| Net weight: | 95 kg |
| Gross weight: | 113 kg |
| Height tank bottom up to centre section: | 550 mm |

| | |
|---|---|
| Set-up area, height: | 1300 mm |
| Required access area, length: | 1240 mm |
| Required access area, width: | 1133 mm |
| Required access area, height: | 580 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| | |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 600 mm |
| Distance pipe bottom inlet to tank bottom: | 670 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 mm |
| Inlet nominal size (OD): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| | |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |
| | |
| Wastewater contents | |
| Separator contents: | 380 l |
| Total volume: | 480 l |
| Contents of sludge trap: | 100 l |
| Storage quantity of grease: | 80 l |
| | |
| Control | |
| Control unit: | no |