

## Grease separator EasyClean free NS 40, Standard

## **Article information**

## **Advantages**

Item no.: 93040.01 GTIN: 4026092103739

• Can be retrofitted up to Auto Mix & Pump

Low-maintenance operation

Price group: 60

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant: Standard Shredder-Mix-System: no

Sludge bucket: no Nominal size (NS): 40 SonicControl: no Refill inlet in accordance with DIN 1988: no

manual with suction hose Type of disposal:

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PF EN 1825 Standard:

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Set-up area, length: 6680 mm Set-up area, width: 1600 mm 1622 mm Set-up area, height: Required access area, length: 6200 mm Required access area, width: 1600 mm Required access area, height: 1622 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom: 1130 mm Distance pipe bottom inlet to tank bottom: 1200 mm Outlet nominal size (OD): 250 mm Outlet nominal size (DN): 250 mm



Inlet nominal size (OD): 250 mm Inlet nominal size (DN): 250 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover
Cover material: Polymer
Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 5000 l
Total volume: 9000 l
Contents of sludge trap: 4000 l
Storage quantity of grease: 1600 l

Control

Control unit: no